

2015 Limited Late Model Rules

IF THESE RULES DON'T SAY "YOU CAN'T", THEN YOU CAN'T

1. Required Driver Equipment

- a. Helmet (Snell approved 2005-2010).
- b. Aluminum racing seat with headrest to roll cage.
- c. Five point safety belt.
- d. Fire suit of flame retardant material.
- e. Fire resistant gloves mandatory.
- f. Fire resistant racing shoes recommended.
- g. Working fire extinguisher required. Must be mounted in approved bracket for that fire extinguisher.
- h. Neck brace required.
- i. Raceceiver mandatory.
- j. Window net.

2. Fuel Cell

- a. Racing fuel cell required and must be mounted by two steel straps two inches wide by 1/8 inch thick around cell. One inch square tubing or pipe must be used frame to frame mounting cell.
- b. Fuel cells must be no lower than rear axle housing and must be enclosed in metal container.
- c. Fuel must be pump type gasoline. Racing gasoline is allowed.
- d. The following are NOT allowed:
 - .. Alcohol
 - .. Additives
 - .. Nitrous Oxide
 - .. Plastic fuel lines

3. Body

- a. 2015 IMCA Late Model dimensions

Chassis and Suspension:

- a. 2015 IMCA Southern Limited Modified rules for chassis and suspension.
- b. Rear end can be GM, Ford 9 inch, or Floater with stock GM mounts. Quick-change rear ends will not be allowed.
- c. No weight jacks.

Wheels

- a. Maximum 10 inch steel wheel.
- b. Bead locks on right rear and right front only.

Tires

- a. Hosier scuffs only. Grooving allowed.

Engine

2015 Imca Limited Modified engine or 2015 Route 66 Street Stock engine will be allowed.

Street Stock Engine rules.

- c. Block must be iron, aluminum blocks are not allowed.
 - d. Screw in rocker studs and tru-roller timing chains are acceptable.
 - e. Small block Chevy must not exceed 366 cubic inches (no strokers) will be pumped to check
 - f. Chrysler must not exceed 372 cubic inch.
 - g. Ford must not exceed 367 cubic inch.
 - h. Heads . the following are NOT allowed:
 - .. Aluminum
 - .. Angle Plug
 - .. Bow Tie
 - .. S.V.O.
 - .. Vortec
 - .. Boss Heads (Fords)
 - .. Iron Eagle heads
 - .. W-2 Mo Par
 - .. Porting, polishing, port matching, or angle milling
 - .. Heads that did not come on a street driven production car
 - .. Aftermarket steel OEM heads are allowed must be stamped S.R or E.Q./IMCA spec head.
 - i. Valve train
 - .. Must be stock type, roller rockers, roller tip rockers, and poly locks are allowed.
 - .. Factory guide plates are allowed.
 - .. Stud girdles are not allowed.
- Street Stock Rules 39
- j. Cam
 - .. Any hydraulic cam.
 - .. Lifter bore must be stock.
 - .. Hydraulic lifters only.
 - .. Roller cams, mushroom cams, and mushroom lifters, hydraulic roller lifters are not allowed.
 - k. Fuel Pump
 - .. Manual only; electric fuel pumps are not allowed. No belt driven pumps.
 - l. Ignition
 - .. Stock typed ignition.
 - .. Mags or aftermarket spark boxes are not allowed.
 - m. Intake
 - .. Cast Iron dual plane or aluminum dual plane. Aluminum manifold can only be 2101 Edelbrock or 52001 Professional Product.

.. The following are not allowed:

.. Bow tie

.. S.V.O.

.. Boss (Ford)

.. W-2 Mo Par

.. Porting, polishing, matching of ports, gutting of intake

.. Marine intakes.

n. Carburetor

.. One carburetor, not to exceed four barrels, stock-type only.

4 barrel 750 part number 3310

Only choke plate may be removed.

.. Carburetor adapter/spacer cannot exceed 1 inch tall.

.. Vacuum secondary Holley's allowed only choke plate may be removed, must be 01850 or 03310 with list number stamped on air horn.

.. The following are NOT allowed:

.. Alcohol

.. Additives

.. Nitrous oxide.

38 Street Stock Rules

o. Stock type starter, mini starter optional. Must be in working order.

p. Steel flywheel.

q. Exhaust-Headers are allowed.

r. Pistons

.. Flat top or dished pistons only. No 2-ring pistons allowed.

.. Maximum overbore is .060

s. Oil Pan

.. Stock or wet sump racing pan only.

.. External oil pumps or dry sump systems are not allowed.

.. No light weight crank shafts, cranks must weigh at least 45 lbs.

Transmission

3 speed set up, Brinn, or Falcon

Automatic is allowed

Any Header allowed

Weight

a. 2,350lbs